



UPS STAND ALONE 10KVA - 30KVA

Features

- Advanced dual-core DSP control technology and 3-level technology
- Active power factor correction (APFC), input power factor up to 0.99
- System efficiency is improved to 96%, energy saving rate is doubled
- Output power factor 1.0
- Dual input design, supporting independent bypass
- Advanced digital and parallel technology, providing higher reliability than single system
- Wide input voltage range
- 50/60 Hz auto-sensing frequency
- 50/60 Hz frequency conversion mode
- Work efficiency up to 98% in ECO mode
- Fan speed varies intelligently with load, reducing noise and extending its service life
- Conformal coating technology to make UPS operate in harsh environment for a long time
- Flexible battery configuration setting, selectable battery numbers: 32~40 pcs
- Digitally controlled charger
- Ability to switch on the UPS by battery in the absence of mains power (Cold start)
- Zero switching time for UPS power supply mode when the mains power is unstable, ensuring the output is uninterrupted
- Compact internal layout, small footprint
- 5 inches LCD colorful touch screen, friendly human & machine interface
- Powerful background software for parameters configuration and online upgrade
- Advanced multi-platform communication for UPS monitoring: RS232, USB, RS485, dry contacts, SNMP card, Wi-Fi card and GPRS card
- Linear derating in low voltage input, reducing battery discharging times, extending the service life of battery
- Intelligent battery management, automatic equalized and float charging control, charger dormancy control, improving the reliability of charger and extending the battery life
- Effective hardware and software protection, robust self-diagnosis function, abundant event logs for future check
- Standard RS232, USB, RS485, EPO, Dry contacts, Parallel port
- Optional SNMP card, Wi-Fi card, GPRS card, SMS alarms

MODEL	KUE 3T10 WB	KUE 3T10 LB	KUE 3T20 WB	KUE 3T20 LB	KUE 3T30 WB	KUE 3T30 LB
Capacity	10kVA / 10kW		20kVA / 20kW		30kVA / 30kW	
INPUT						
Rated voltage	380 / 400 / 415 Vac (L-L)					
Voltage range	304~478Vac (L-L),full load 228V~304Vac (L-L), load decrease linearly according to the min phase voltage					
Rated frequency	50 / 60 Hz					
Frequency range	40 ~ 70 Hz					
Power factor	> 0.99					
Bypass voltage range	Selectable, default -20% ~ +15% Up limited: +10%, +15%, +20%, +25 %; Down limited: -10%, -15%, -20%, -30%, -40%					
Bypass frequency range	Selectable, ±1Hz, ±3Hz, ±5Hz					
Input current THDi	<3% (linear load)					
Bypass overload	125%: long term operation; 125% ~ 130%: 10min; 130% ~ 150%: 1min; 150% ~ 400%: 1s; >400%, less than 200ms					
OUTPUT						
Rated voltage	380/ 400/ 415 Vac (L-L)					
Voltage precision	± 1% (linear load)					
Frequency	Synchronized with utility in mains mode, 50/60 Hz ± 0.1% in battery mode					
Waveform	Sinusoidal					
Power factor	1					
Total harmonic distortion (THDv)	< 1% (full linear load), < 3% (full non-linear load according to IEC/EN62040-3)					
Crest factor	3:1					
Overload	<110%, 60min; 110% ~ 125%, 10 min; 125% ~ 150%, 1min; > 150%, 200ms					
BATTERIES						
DC voltage	±120VDC	±240VDC (selectable, 32 - 40pcs)	±240VDC	±240VDC (selectable, 32 - 40pcs)	±180VDC	±240VDC (selectable, 32 - 40pcs)
Number of battery	(10+10) x 9AH	/	(20+20) x 9AH	/	(15+15) x 9AH x 2 strings	/
Charging current	10 A Max.					
Recharge voltage precision	1%					
SYSTEM						
Display	5 inches touch screen					
Efficiency	95% Max.					
Transfer time	0ms					
Interface	Standard: RS232, RS485, USB, battery cold start Option:programmable dry contact, SNMP, parallel kit					
ENVIRONMENT						
Operating temperature	0°C ~ 40°C					
Storage temperature	-40°C ~ 70°C					
Relative humidity	0 ~ 95% (non-condensing)					
Altitude	<1000m, load derated 1% per 100m from 1000 ~ 2000m					
Noise level at 1 m	58dB Max.				62dB Max.	
OTHERS						
Dimensions (W x D x H)(mm)	250 x 720 x 560	250 x 720 x 560	250 x 800 x 700	250 x 720 x 560	250 x 840 x 930	250 x 840 x 650
Packaged dimensions (W x D x H) (mm)	350 x 800 x 722	350 x 800 x 718	350 x 900 x 862	350 x 800 x 718	350 x 950 x 1102	350 x 980 x 810
Net weight (kg)	82	31	145	33	215	42
Gross weight (kg)	93	40	156	42	227	52

- Wb means standard model; Lb means long time model.
- Custom-made specifications are acceptable.
- All specifications are subject to change without notice